

Accessories

JNIOR



Power Supply

Catalog Number	PSA-120-125
Input	<p>Rated Input Voltage 100 V - 240 V ac</p> <p>Input Voltage Range 90 V - 264 V ac</p> <p>Rated Frequency 50 V - 60 Hz</p> <p>Frequency Range 47 V - 63 Hz</p> <p>Rated Input Current 300 mA RMS max.</p> <p>Inrush Current 15 A max. at 115 / 30 A max. at 230 V ac cool start</p>
Output	<p>Output Voltage 12 V dc at 1.0 A</p> <p>Output Min. Current 0 A</p> <p>Line Regulation ± 1%</p> <p>Load Regulation ± 5%</p> <p>Over Voltage Protection; 15 ~ 18 V dc max. (output shutdown)</p> <p>Short Circuit Protection: Output Shut Down and Auto Restart</p> <p>Ripple Voltage 150 mV (p-p) (100 - 240 V at Full Load)</p> <p>Efficiency: 60% min.</p>
Safety and EMI	<p>HI POT Input to output (3000 V ac at 10 mA for 1 min.)</p> <p>Insulation Resistance: Input to output (> 100 M Ohm at 500 V dc)</p> <p>Safety Approvals UL/cUL</p> <p>EMI Standard Meets FCC class B, VCCI:II</p> <p>RoHS Compliant: Yes</p> <p>Leakage Current 0.25 mA</p>